

## QUICK TECH TT42

**Kind :** CNC lathe  
**Brand :** QUICK TECH  
**Model :** TT42  
**Year :** 2011  
**Serial Nr:** 2935  
**Stock Nr :** T14426



### TECHNICAL DETAILS

- Number of axes : 8
- Number of spindles : 2
- Number of turrets : 2
- MAIN SPINDLE
- Spindle nose : A2-5
- Spindle power : 7,5 [kW]
- Spindle speeds : 6.000 [rpm]
- Max. bar diameter : 42 [mm]
- Max. turning length : 230 [mm]
- C axis indexing precision : 0,001 [°]
- COUNTER-SPINDLE
- Spindle nose : A2-5
- Spindle power : 3,7 [kW]
- Spindle speeds : 6.000 [rpm]
- Max. bar diameter : 42 [mm]
- Max. turning length : 100 [mm]
- C axis indexing precision : 0,001 [°]
- Z stroke : 360 [mm]
- X stroke : 410 [mm]
- TOOL BLOCK SYSTEM 1
- Number of positions : 16
- Number of motorized positions : 6
- X/Z stroke : 140 x 230 [mm]
- Y stroke : 410 [mm]

**Kind : CNC lathe**  
**Brand : QUICK TECH**  
**Model : TT42**  
**Year : 2011**  
**Serial Nr: 2935**  
**Stock Nr : T14426**

- Tool type : ER20  
- Live tools speed : 4.000 [rpm]  
- Live tools power : 1 [kW]

**TOOL BLOCK SYSTEM 2**

- Number of positions : 15  
- Number of motorized positions : 6  
- Y stroke : 410 [mm]  
- Tool type : ER 20  
- Live tools speed : 4.000 [rpm]  
- Live tools power : 1 [kW]

**POWER SUPPLY**

- Supply voltage : 380 [V]  
- Total installed power : 20 [kVA]

**WEIGHT & DIMENSIONS**

- Machine floor space : 3.465 x 1.654 [mm]  
- Machine height : 1.896 [mm]  
- Machine weight : 4.200 [kg]

**MACHINE HOURS**

- Number of hours under power : 10363 [h]  
- Number of working hours : 7359 [h]

**EQUIPMENT**

- CNC : Mitsubishi M700  
- Interface : Ethernet / RS232 / USB / PCMCIA  
- 3 colors status lamp  
- Coolant tank  
- Chips conveyor  
- Parts catcher  
- Parts conveying strip  
- Collet chuck : 2x BELLEGRANDI 48F